


**Wireless VoIP Phone(uVP-500) Specification**

Specifications	Contents
VoIP Protocol	SIP(RFC3261)
Voice Codec	G.729A/G.711, G.168 Echo Canceller
Voice Packet Size	G.711(10/20/30msec), G.729(20~80msec)
Battery	1120mAH, Li Polymer Battery
Battery Service Time	Talk : 3.5 Hours, Standby : 70 Hours
Wireless Access Protocol	CSMA/CA
Security	WEP 64/128, WPA-PSK
Frequency	2.4 ~ 2.483 GHz
W-LAN	IEEE802.11b/g, Multi Profile [4]
Firmware Upgrade	Air Remote Firmware Upgrade : FTP
RF Power	> 16 dBm (802.11b), > 14 dBm(802.11g)
Distance	Open space : 250m, Indoor : > 20m
<b>Phone Features</b> 	Phone book [150]
	Call History [20]
	Distinctive Ringing [8]
	Call Time Display, Dialed number display, Redial
	DTMF signaling (In-band, RFC2833)
	Call Transfer, Call Holding, Call Waiting, Call Forwarding
	Mute, Keypad Lock
	SMS(Short Message Service)
	e-mail
	Configuration Phone GUI , WEB server
	Language : English, Korean
	128*128 65K Color STN LCD
	8MB Flash, 32 MB SDRAM
	Blue Back light on Keypad
	Cradle, Adaptor (5V)
	Phone : 46 x 152 x 27 mm
	Cradle : 80 x 78 x 60 mm